

TECHNICAL SPECIFICATIONS

TEC CRYSTAL BUS

It is a calendered PVC film monomeric crystal with custom texture which refers to metal decking, liner siliconized adhesive and permanent acrylic coated paper.

Indication: For scanned images applied for flooring protection, creating a metal floor texture; where there is low to medium traffic. Application suitable for flat and smooth surfaces, resistant to light impacts.

Physical Property: Front: PVC calendered 400µm (microns).
Liner: coated siliconized paper 120 g/m².
Adhesive: Acrylic Permanent 20 g/m² (± 2g/m²).

Supply and

- Material packed in cardboard boxes and coils with widths of 1.22m.

Durability:

- Expected durability: 12 months for outdoor use.
Important: the durability can be extended or decreased as a result of application techniques and conservation. Alltak can't be responsible for printing durability.

Storage:

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.
Validity: two years starting from manufacturing date, provided it is in original packaging and appropriate location.

Recomendations:

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the film for special applications, we recommend customers to conduct their own testing.

Note: our products are not part of the production chain of auto parts and building materials.