

TECHNICAL SPECIFICATION KRUSHER

It is a calendered PVC film POLYMERIC with special texture, available in the colors: white, black, graphite, red, silver, military green and blue metallic. Paper liner coated siliconized and repositionable acrylic adhesive.

Indication:	Designed for protection and customization of vehicles, can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.
Physical Property:	Front: PVC compounder 100 micron (0,10 μ m). Liner: Coated siliconized paper 150 g/m ² . Adhesive: acrylic repositinable 17 g/m ² (+ 2g/m ²).
<u>Supply and</u> <u>Durability</u> :	 Material packed in box and cardboard reels with a width of 1.38m. Expected durability: seven years (except color graphite and blue metallic – one year). In horizontal this durability is reduced to 30%. <u>Important</u>: durability can be extended or decreased as a result of application techniques and conservation.
<u>Storage</u> :	Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%. Validity: two years from the date manufacture if packed in original packaging and in an appropriate place.
<u>Recomendations</u> :	 Apply in smooth superfice; cleaned with isopropyl alcohol avoiding contact with impurities, oils or any other chemical. Do not use in places with ripples, rough surfaces and/or porous. Excess solvent usage reduces the durability of the product of time. Install immediately after cutting. Once applied to avoid aggressive products and constant friction.
 and do not cons Due to diversit recommend cus 	a are based on laboratory tests that Alltak believes to the reliable and are provided for informational purposes only stitute any form of guarantee. ty of potential influencing factors during application and use of the adhesive film for special applications, we stomers to conduct their own testing. ucts are not part of the production chain of auto parts and building materials.
	EPA 39 - Review 05 – 03/01/2018 Page: 1/1



TECHNICAL SPECIFICATION KRUSHER METALLIC

It is a calendered PVC film POLYMERIC with special texture, available in two colors: gold and rose. Paper liner coated siliconized and repositionable acrylic adhesive.

Indication:	Designed for protection and customization of vehicles, can be used for clipping. Good stability
	on smooth surfaces and curves, resistant to light impacts.
Physical Property:	Front: PVC compounder 250µm (microns).
	Liner: Coated siliconized paper 150 g/m ² .
	Adhesive: acrylic repositinable 17 g/m ² (+ 2g/m ²).
Supply and	 Material packed in box and cardboard reels with a width of 1.38m.
Durability:	• Expected durability: 1 year. In horizontal this durability is reduced to 30%.
	Important: durability can be extended or decreased as a result of application techniques and conservation.
<u>Storage</u> :	Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.
	Validity: two years from the date manufacture if packed in original packaging and in an appropriate place.
Recomendations:	 Apply in smooth superfice; cleaned with isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
	 Do not use in places with ripples, rough surfaces and/or porous.
	• Excess solvent usage reduces the durability of the product of time.
	Install immediately after cutting.
	Once applied to avoid aggressive products and constant friction.
and do not consti → Due to diversity recommend custo	are based on laboratory tests that Alltak believes to the reliable and are provided for informational purposes only itute any form of guarantee. of potential influencing factors during application and use of the adhesive film for special applications, we omers to conduct their own testing. cts are not part of the production chain of auto parts and building materials.
	EPA 43 - Review 03 – 03/01/2018 Page: 1/1