

TECHNICAL SPECIFICATION

TEC PROTECTION MASK

It is a calendered PVC film MONOMERIC translucent blue, liner siliconized coated and removable acrylic adhesive.

Indication: Electronic clippings transfer with medium formats, electrical protection and mask painting.

Physical Property: Front: PVC calendered 80µm (microns).
Liner: coated siliconized paper 120 g/m².
Adhesive: Acrylic removable 15 g/m² (± 2 g/m²).

Supply and • Material packed in cardboard boxes and coils with widths of 1.00 m.

Durability: • Expected durability: six months.
Important: the durability can be extended or decreased as a result of application techniques and conservation.

Storage: Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.
Validity: two years starting from manufacturing date, provided it is in original packaging and appropriate location.

Recommendations:

- Apply in smooth, flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and / or porous.
- Excess solvent usage reduces the durability of the product of time.
- Suitable for installation immediately after cutting.
- Once applied avoid aggressive products and constant friction.
- We do not guarantee product properties in case of reuse of the material.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.
Note: our products are not part of the production chain of auto parts and building materials.