

## **TECHNICAL SPECIFICATION**

### **COLOR REMOVABLE TRANSPARENT**

It is a calendered PVC film MONOMERIC whit high brightness, transparent, siliconized liner and adhesive permanent acrylic.

**Indication:** General use as signage, advertising, design, decoration, identification fleets, electronic clipping, cutting and creasing.

**Physical Property:** Front: PVC compounder 80µm (microns).  
Liner: coated paper siliconized 120 g/m<sup>2</sup>.  
Adhesive: Acrylic Permanent 15 g/m<sup>2</sup> (± 2g/m<sup>2</sup>).

**Supply and**

- Material packed in cardboard boxes and coils with widths of 1.00m.

**Durability:**

- Expected durability: three years for outdoor use.  
Important: the durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.  
Validity: two years starting from manufacturing date, provided it is in original packaging and appropriate location.

**Recomendations:**

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the film for special applications, we recommend customers to conduct their own testing.  
Note: our products are not part of the production chain of auto parts and building materials.

# ALLTAK®

LINHA DE ADESIVOS PARA COMUNICAÇÃO VISUAL